

Data Sheet PERC Flexible Solar Panel

LINKSOLAR

Jinjing Kejigu Wuqiing,
Chaku , Tianjin City, China
13706774101 ,info@Lnk-solar.com

Efficiency 23-24.5%,thickness 3mm, general 200-500watt single panel shipping cost is very high do not recommend personal to order.

Power (W)	Matrix (solar cell)	Vmp (V)	Imp (A)	Voc (V)	Ics (A)	Back Dimensions (mm)	Front Dimension s (mm)	Weight (kg)
55W	182 solar cell (4*2)	8.96	6.13	10.75	6.63	765*395	785*395	0.95
85W	182 solar cell (4*3)	13.44	6.33	16.12	6.83	765*585	785*585	1.67
115W	182 solar cell (4*4)	17.92	6.45	21.50	6.95	765*765	795*765	2.22
140W	182 solar cell (5*4)	22.40	6.27	26.88	6.75	960*765	980*765	2.75
155W	166 solar cell (9*3)	30.24	5.13	36.28	5.56	1580*550	1600*550	3.25
180W	182 solar cell (5*5)	28.0	6.44	33.60	6.94	960*960	980*960	3.50
215W	182 solar cell (6*5)	33.60	6.40	40.32	6.94	1140*960	1160*960	4.12
250W	182 solar cell (7*5)	39.20	6.40	47.04	6.94	1325*960	1345*960	4.75
285W	182 solar cell (8*5)	44.80	6.40	53.76	6.94	1510*960	1530*960	5.35
300W	166 solar cell (9*6)	30.0	10.10	36.0	10.50	1550*1050	1570*1050	6.02
320W	182 solar cell (9*5)	50.40	6.35	60.48	6.85	1695*960	1715*960	6.10
355W	182 solar cell (10*5)	56.0	6.35	67.20	6.85	1880*960	1900*960	6.75
430W	182 solar cell (10*6)	67.20	6.40	80.64	6.91	1880*1140	1900*1140	8.05
460W	210 solar cell (8*6)	53.76	8.68	63.6	9.11	1735*1300	1750*1300	8.50
500W	182 solar cell (10*7)	78.40	6.38	94.08	6.37	1880*1325	1900*1325	9.25